

# Technical specifications

Engine	Volvo 6 cylinder 345 kW (469 hp) EU fase IIIB
Operational RPM	1200 - 1500 RPM
Fuel tank capacity	900 litre
Hydraulic pumps	Linde
Wheel motors	Linde
Control	EcoTronicPlus
Drive	Stepless hydrostatic with speed control
Steering	On all four wheels
Auto steering	Front and rear
Working width	6 rows 45 or 50 cm ( <i>18" oder 20"</i> )
Defoliators	Integral, or with side delivery + spreader
Scalpers	ProtectPlus, adjustable from the cab
Lifting system	ExcenterPlus, horizontal row seeking
Depth control	Automatic
Lifting turbines	2 x 1.500 mm
Cleaning turbine	3 x 1.550 mm ( <i>option: a 4th cleaning turbine</i> )
Ring elevator	1.000 mm wide
Gates	Pigtail gates and/or bar gates
Bunker	18,5 m <sup>3</sup>
Discharge elevator	1.000 mm
Tank Unloading time	Ca. 1 minute
Tracks <i>OptiTraxx</i>	760 mm wide, 2.300 mm high
Front tires <i>LightTraxx</i>	710/75 F34
Rear tires	750/65 R26
Greasing system	Automatic system ' <i>BEKA-MAX</i> '
Transport width	3,25 m
Height	4,00 m
Length	11,30 m ( <i>depending of the lifting syste</i> )
Weight	20 ton
Chassis	Rear wheels driving in-between the tracks of the front wheels ( <i>good for soil</i> )

Agrifac Machinery B.V.  
Eesveenseweg 15  
8332 JA Steenwijk  
The Netherlands

Changes in relation to technical progress reserved. Approved by TÜV and Berufsgenossenschaft; in compliance with the CE-regulations. No liability for misprints.

Phone: +31 (0) 521 - 527 210  
Fax: +31 (0) 521 - 517 328  
Email: [info@agrifac.com](mailto:info@agrifac.com)  
Website: [www.agrifac.com](http://www.agrifac.com)